B&NES Parking Standards Accessibility Assessment

Stage 1:

Identify basic parking standard for the land use based on the quantum of development. Complete key details about the proposed development below.

Proposed Development	
Name of development	
Development location	
Parking Standard Zone	
Does the site location broadly reflect the characteristics of the Zone to which it falls into? If no, please provide a reason	
Brief description of development including land use and quantum of development	
Does the development comprise origin or destination parking*?	
Car parking provision based on standards set out in Chapter 5	

*Where a proposed mixed-use development comprises both origin and destination parking (i.e. residential and non-residential elements), a separate Accessibility Assessment should be completed for each.

Stage 2:

Complete all questions put forward in the questionnaire below.

A guide for the scoring criteria for completing the Accessibility Assessment questionnaire is provided for each mode of travel. This is not exhaustive for all questions, but is designed to provide some examples against which to score the proposed development in terms of accessibility. Where questions are deemed to require a binary response, the score should reflect the extent to which the site is accessible relevant to the question.

Where a future transport scheme has been commissioned and its delivery is guaranteed, this should be accounted for as part of the appropriate section within this Accessibility Assessment dependent on the impacted mode of travel.

		Walking				
	Score 1	Score 3	4 Score 5	5		
	Poor Accessibility	Moderate Accessibility	Good Acces			
Criteria	 No footways or pedestrian crossings adjacent to the site Pedestrians use an access where vehicles have priority No access provided for all users, including wheelchair / pushchair users or those with mobility impairments Access to the site is indirect from the wider offsite active travel network No street lighting of disabled access Limited number of and access to local facilities* 	 Footways present are of an adequate width, typically with a width of around 1.5m Some pedestrian crossing facilities provided Access to the site partially aligns with the wider off-site active travel network Access for all users provided is adequate, including wheelchair / pushchair users or those with mobility impairments Pedestrian routes are maintained to a reasonable standard, with some street lighting, reasonable surface conditions and disabled facilities Limited number of local facilities* but with good access, or adequate access but to a good range of facilities 	 Footways presen comfortable width least 2.0m wide Pedestrian crossi provided at approon pedestrian des Access to the site with the wider off travel network Good access for provided, includin wheelchair / push or those with mol impairments Pedestrian routes maintained, well lis up to standard designated wheel pushchair access Access to and rai facilities* is good 	ings spriate place sire lines e aligns well esite active all users g schair users schility s are well lit, surfacing and there is lichair /		
	* Consideration should be given to ac and healthcare facilities	ccess to facilities including employment, for	ood outlets, education, places o	of worship,		
	Is there good accessibility to e	ducation facilities on foot?		/ 5 / 5		
	Is there good accessibility to employment facilities on foot?					
	Is there good accessibility to retail facilities on foot? Is there good accessibility to healthcare facilities on foot? (e.g. GP, Pharmacy)					
		sed development, is the footway		/ 5 / 5		
	terms of the presence of footw		p			
	Are suitable pedestrian crossil lines to and from the site to ke	ng points provided to accommoda y attractions?	ate pedestrian desire	/5		
		ufficient level of access provided	for pedestrians	/5		
	Is there suitable access provide	led to the site, for those with mob	ility impairments?	/ 5		
	Is the pedestrian infrastructure	well maintained?		/ 5		
	·	afe and perceived to be safe, ber and well lit, with street lighting pro		/ 5		
		ocal facilities on foot, relevant to t	he proposed	/5		
		provided e.g. conveniently located es?	d benches, on-site	/ 5		
			Total Walking	/ 60		

		Cycling			
	Score 1	2 Score 3	4 Score 5		
	Poor Accessibility	Moderate Accessibility	Good Access	ibility	
Criteria					
	facilities	to education facilities by cycle?		/ 5	
		to employment facilities by cycle?		/5	
	Is there good accessibility			/ 5	
		to healthcare facilities by cycle? (e.g	, GP, Pharmacy)	/5	
		king on site acceptable, including to		/5	
		ality (i.e. covered, secure, weatherp	roof, robust and in good	/5	
	Is cycle parking provided in a suitable location, in line with the requirements set out in Chapter 7 of the Transport and Development SPD and in line with LTN1/20?				
	Is safe access for cyclists provided into the site?				
	Are safe and inclusive access routes for cyclists provided to and from the site, to				
	accommodate all cycling competencies and non-standard cycles, allowing integration				
	into the wider off-site active travel network?				
	Is there good accessibility	to local facilities by bicycle?		/ 5	
			Total Cycling	/ 50	

Score 1 2 Score 3 4 Score 5				Bus			
 Walking distance to nearest bus stop >800m Frequency of principle bus service is likely, >60 mins, or does not offer services at times suitable to proposed site users** Distance to nearest bus stop aligns with requirements of proposed site users** Distance to nearest interchange with 5 or more routes is >1200m Nearest bus stop is marked only by a flag and pole, limited or no timetable information, little or no street lighting, <1.5m wide footway **Bus service provision should ensure that timings will align with the intended development purpose such as in time for staff to arrive with sufficient time before registration in the case of a school, or at suitable shift changeover or commuter times for non-residential developments. Walking distance to nearest bus stop sus top 400-800m Frequency of principle bus service aligns well with requirements of proposed site users** and is likely <15 mins Distance to nearest bus station / major interchange with 5 or more routes is 800-1,200m Nearest bus stop is marked by a building, with timetable information, and adequate footway and lighting provision Nearest bus stop is marked by buildings **Bus service provision should ensure that timings will align with the intended development purpose such as in time for staff to arrive with sufficient time before registration in the case of a school, or at suitable shift changeover or commuter times for non-residential developments. Is a bus stop provided within an acceptable walking distance? Are bus stop facilities provided at the nearest stop of a good standard? 		000.0	2	000.00	4	333.33	
staff to arrive with sufficient time before registration in the case of a school, or at suitable shift changeover or commuter times for non-residential developments. Is a bus stop provided within an acceptable walking distance? Is bus service provision at a suitable frequency and time to serve the proposed / 5 development? Is a bus interchange (with 5 or more routes) provided within an acceptable walking / 5 distance? Are bus stop facilities provided at the nearest stop of a good standard? / 5	Criteria	Walking distance to nearest bus stop >800m Frequency of principle bus service is likely, >60 mins, or does not offer services at times suitable to proposed site users** Distance to nearest interchange with 5 or more routes is >1200m Nearest bus stop is marked only by a flag and pole, limited or no timetable information, little or no street lighting, <1.5m wide footway		Walking distance to nearest bus stop 400-800m Frequency of principle bus service at nearest bus stop aligns with requirements of proposed site users** but is likely <30 mins Distance to nearest bus station / major interchange with 5 or more routes is 800-1,200m Nearest bus stop is marked by a bus shelter and flag, with timetable information, and adequate footway and lighting provision		 Walking distance bus stop <400m Frequency of print service aligns well requirements of pusers** and is like Distance to nearestation / major into with 5 or more rouse800m Nearest bus stop shelter, seating a timetable informativets, adequate for width and street lighas CCTV or is on by buildings 	to nearest ciple bus I with roposed site ly <15 mins st bus erchange ites is has a nd flag, cion, raised cotway ghting and verlooked
Is bus service provision at a suitable frequency and time to serve the proposed development? Is a bus interchange (with 5 or more routes) provided within an acceptable walking /5 distance? Are bus stop facilities provided at the nearest stop of a good standard? /5		staff to arrive with sufficient times for non-residential develo	e before re opments.	gistration in the case of a school,	or at suita		commuter
distance? Are bus stop facilities provided at the nearest stop of a good standard? / 5		Is bus service provision at				proposed	
		distance?					/5
		Are bus stop facilities prov	rided at t	he nearest stop of a good s	tandard	? Total Bus	/ 5 / 20

			Rail			
	Score 1	2	Score 3	4	Score 5	5
	Poor Accessibility		Moderate Accessibility		Good Access	sibility
Criteria	Walking distance to nearest rail station >2,000m Services per hour per direction from nearest station within 1.2km walking distance is 1-2 services Nearest rail station has few facilities with no waiting facilities, no toilets, timetables only, unstaffed, no security measures, no retail facilities, no disabled accessibility and no taxi rank		 Walking distance to nearest rail station <1,200m Services per hour per direction from nearest station within 1.2km walking distance is 3 to 4 services Nearest rail station has part enclosed waiting facilities, toilets, timetables and real time information, ability to purchase tickets part-time staffing, CCTV and other security measures, some retail facilities, some disabled accessibility and taxi rank 		 Walking distance rail station <800m Services per hour direction from neawithin 1.2km walk is 5 or more service Nearest rail station heated and encloy facilities, toilets, ti and real time inforticket office and mostaffed the majoritic day, CCTV and or measures, good measures, good measures, good measures, good measures, bus and te interchange within proximity 	r per rest station ing distance ces n has sed waiting metables rmation, nachines, ty of the ther security ange of y ts and axi
	Is a rail station provided w	thin an	acceptable walking distance?)		/ 5
		-	provision per direction per hou	r?		/ 5
	What level of rail station fa	cilities	are provided?			/ 5
					Total Rail	/ 15

		Ad	ditional Considerations			
	Score 1	2	Score 3	4	Score 5	5
	Poor Accessibility		Moderate Accessibility		Good Access	sibility
Criteria	accounted for within this Access Site users will not have access to a car club The roads within ~400m of the site are not part of a CPZ. As such vehicles associated with the site could park on surrounding roads. Significant risk that over-spill parking could result in issues such as pavement parking, or impeding emergency, delivery and refuse vehicles.	ibility Ass	Some or all of the roads within ~400m of the site are not part of a CPZ. As such vehicles associated with the site could park on some of the surrounding roads. However, there is a low risk that overspill parking would result in issues such as pavement parking, or impeding emergency, delivery and refuse vehicles.		 All site users will I to a car club The majority of rowald a CPZ. As such it unlikely that vehic associated with the be able to park or surrounding roads 	have access ads within are part of is highly les e site would
	·		the site are subject to CPZs	?		/ 5
	What level of car club serv	vice is a				/5
			Total A	Additiona	al Considerations	/ 10

Stage 3:

Calculate the accessibility score as a percentage for: Active Travel (walking and cycling sections); and Public Transport & Additional Considerations (bus, rail and additional considerations sections). Convert these scores into a percentage.

	Active	Travel	Public Transport and Additional Considerations			
	Walking Cycling		Bus Rail		Additional Considerations	
Scores	/ 60 / 50		/ 20	/ 15	/ 10	
Sum all scores		/ 110		/ 45		
Combined Accessibility Score (%)	%		%			

Stage 4:

Identify the potential appropriate parking reduction based on the questionnaire scores, using the accessibility matrix. Complete the key outcomes from this assessment in the Accessibility Assessment Stage 4 – Summary table.

		Active Travel Accessibility Score				
		0-25%	25-50%	50-75%	75-100%	
	0-25%	No discount fro	om standards	No discount fr	rom standards permitted	
Public Transport and Additional	25-50%	permi	tted	Up to 30% reduction.	Up to 30% reduction.	
Considerations Accessibility Score		50-75%	No discount	Up to 15% reduction.	Up to 25% reduction.	Up to 35% reduction.
	75-100%	permitted	Up to 20% reduction.	Up to 35% reduction.	Up to 100% reduction - Scope for a car free development.	

Notes:

- Discounts to the maximum car parking provision apply to standard car parking spaces only. The
 provision of disabled parking spaces should be calculated based on the parking standards set out in the
 Transport and Development SPD, prior to any discounts being applied.
- Similarly, the requirement for cycle, scooter and PTWs should be based on the development quantum
 or car parking prior to any discount being applied to the maximum car parking provision. Where
 significantly reduced levels of parking are proposed, sufficient levels of cycle parking will need to be
 provided.
- Should a parking discount be proposed by the developer, it is required to demonstrate how on-road parking will be managed within the vicinity of the site, to ensure that parking pressure is not simply offset to another area.

Accessibility Assessment Stage 4 – Summary

Proposed Development	
Brief description of development	
including land use and quantum of	
development	
Car parking provision based on	
standards set out in Chapter 5 (spaces)	
Active Travel Accessibility Score	
Public Transport and Additional	
Considerations Accessibility Score	
Potential discount from standards (%)	
Proposed discount from standards for	
development (%)	
Proposed parking provision after	
accessibility discount (spaces)	

Stage 5:

Following completion of this Accessibility Assessment, the findings should be shared with the Local Highway Officer to initiate further discussion regarding the parking provision for a proposed site.